

CRACK PROPAGATION STOPS FOR DICING OF PLANAR LIGHTWAVE CIRCUIT DEVICES

5

Field of the Invention

The present invention generally relates to fabricating and dicing optical integrated circuits. In particular, the present invention relates to efficiently
10 isolating optical integrated circuits with high yields from substrates.

Background of the Invention

Planar lightwave circuits (PLCs) are optical circuits laid out on a silicon wafer. PLCs, which typically contain one or more planar waveguides often used
15 in arrayed waveguide gratings, are used as components in constructing an optical communication system. Optical communication systems permit the transmission of large quantities of information. With ever increasing internet traffic, greater demands are placed on optical communication systems, and their corresponding components.

20 A plurality of optical integrated circuits (OICs) including PLCs are typically fabricated on a single substrate or wafer. For example, a substrate may be fabricated with 30 to 40 OICs thereon. Individual OICs are isolated using a specialized saw to dice the substrate. However, OICs have a regular (consistent), non-rectangular geometry. Straight-line dicing using a saw
25 consequently leads to the inefficient isolation of individual OICs from a substrate. Referring to Fig. 1, a substrate 100 with a plurality of PLCs 102 thereon is shown. Referring to Fig. 2, when individual PLCs 102 are isolated from the substrate 100 using a saw (square dicing), several PLCs 104 are destroyed while only one PLC 106 is recovered. Often times, two to four PLCs are destroyed for each PLC that
30 is recovered.

A019

There have been attempts to realize increased yields of OICs from optical component substrates using laser cutting techniques and water jet stream cutting techniques. These techniques are attractive because they in theory permit curvilinear cutting of non-rectangular shapes is possible.

5 Referring to Figure 3, an OIC 120 diced using curvilinear cutting from a substrate containing a plurality of OICs thereon is shown (such as from the substrate shown in Fig. 1). Unfortunately, an OIC 110 cut in a curvilinear manner from a substrate often undesirably contains cracks 112 and chips 114. Such cracks 112 and chips 114 often constitute in fatal defects in the OIC 120 since
10 the cracks 112 and chips 114 inhibit reliable operation of the optical components formed on the OIC.

Moreover, unlike machining metal substrates, OIC substrates and the components thereon are often made of monocrystalline silicon, silicon dioxide, various oxides and silicates, and other materials that are very brittle by nature.
15 The brittle nature of such materials facilitates the formation of cracks and chips in the substrate or the components thereon during cutting. Thus, the propensity to form cracks and chips during curvilinear cutting in combination with the brittle nature of the OIC substrates leads to the low yield of OICs from OIC substrates. And since a plurality of OICs are fabricated in close proximity to one another,
20 even small chips and cracks can render the OICs fatally defective.

There is an unmet need in the to art to improve the current yields of OICs/PLCs from substrates, and particularly to mitigate cracking and chipping when dicing the substrates containing a plurality of OICs/PLCs.

25

Summary of the Invention

The following presents a simplified summary of the invention in order to provide a basic understanding of some aspects of the invention. This summary is not an extensive overview of the invention. It is intended to neither identify key or critical elements of the invention nor delineate the scope of the invention.

A019

Rather, the sole purpose of this summary is to present some concepts of the invention in a simplified form as a prelude to the more detailed description that is presented hereinafter. The present invention provides methods and OICs for facilitating curvilinear cutting of OICs substrate with high yield. The present
5 invention provides methods and OICs for facilitating curvilinear cutting of OIC substrates while mitigating or eliminating edge chipping, cracking, and other degrading effects. In particular, providing waveguide stop cracks improves the cut quality of OICs. As a result, the present invention maximizes the yield of non-rectangular OICs from a single substrate. The present invention also
10 correspondingly promotes maximizing the number of non-rectangular OICs that may be fabricated on a single substrate since isolation thereof in high yield is enabled.

One aspect of the invention relates to a method of increasing optical integrated circuit yield per wafer, involving providing a wafer with a plurality of
15 non-rectangular shaped optical integrated circuits; forming stop cracks in the wafer, each stop crack adjacent one of the non-rectangular shaped optical integrated circuits; cutting the wafer in a curvilinear manner to yield a plurality of separated non-rectangular shaped optical integrated circuits.

Another aspect of the present invention relates to a method of dicing a
20 substrate containing a plurality of non-rectangular shaped optical integrated circuits, involving forming stop cracks in the wafer, each stop crack adjacent and substantially parallel one of the non-rectangular shaped optical integrated circuits, and cutting the substrate in a curvilinear manner substantially parallel to a stop crack.

25 Yet another aspect of the present invention relates to an optical structure containing a substrate; a plurality of non-rectangular shaped optical integrated circuits on the substrate, each non-rectangular shaped optical integrated circuit having an active region; and at least one stop crack positioned adjacent each non-rectangular shaped optical integrated circuit.

A019

Still yet another aspect of the invention relates to an optical integrated circuit containing a substrate having two curvilinear longitudinal edges, a non-rectangular shaped active region containing optical components, and at least one stop crack positioned substantially parallel and proximate one of the curvilinear longitudinal edges.

To the accomplishment of the foregoing and related ends, certain illustrative aspects of the invention are described herein in connection with the following description and the annexed drawings. These aspects are indicative, however, of but a few of the various ways in which the principles of the invention may be employed and the present invention is intended to include all such aspects and their equivalents. Other advantages and novel features of the invention will become apparent from the following detailed description of the invention when considered in conjunction with the drawings.

Brief Summary of the Drawings

Fig. 1 illustrates a top-down view of an OIC substrate with a plurality of OICs thereon.

Fig. 2 illustrates a conventional manner of cutting an OIC substrate.

Fig. 3 illustrates problems with cutting an OIC substrate.

Fig. 4 illustrates OICs diced in accordance with one aspect of the present invention.

Fig. 5 illustrates an OIC diced in accordance with one aspect of the present invention.

Detailed Description of the Invention

The present invention involves forming stop cracks in an OIC substrate to facilitate curvilinear cutting of the OICs from a brittle substrate while minimizing/controlling chipping and cracking of the OIC and substrate. Referring again to Fig. 1, a substrate 100 with a plurality of PLCs 102 thereon is shown.

A019

Referring now to Fig. 4, all or substantially all of the individual PLCs 102 may be cut and isolated from the substrate 100 with high yield. Curvilinear cutting between stop cracks is conducted to separate the non-rectangular shaped optical devices from each other while mitigating damage to the active region of the OICs.

Referring to Fig. 5, an OIC 200 in accordance with one aspect of the present invention is shown. OIC 200 is non-rectangular in shape and has active region 202 where various optical components are positioned (such as lenses, taps, optical ports, waveguides, multiplexers, demultiplexers, AWGs, and the like), at least one and preferably two waveguide stop cracks 204 positioned substantially parallel with the longitudinal edge of the OIC, and sacrificial regions 206 positioned between the longitudinal edge and the waveguide stop cracks 204. The stop cracks 204 are positioned not only substantially parallel with the longitudinal edge of the OIC 200, but also proximate the longitudinal edge of the OIC 200 to facilitate increased integration (maximizing the number of OICs formed on a given substrate). Although only one OIC is shown, typically a substrate is fabricated with about 2 to about 50 OICs thereon.

The presence of the waveguide stop cracks 204 reduces the propensity of cracks 208 and chips from degrading the active region 202 of the OIC 200. In other words, cracks 208 and chips created by curvilinear dicing do not spread out of the sacrificial regions 206 into the active region 202 of the OIC 200 because the stop cracks 204 contain and/or isolate the cutting induced defects to the sacrificial regions 206.

The substrates with OICs thereon that are cut in accordance with the present invention are made, at least in part, with brittle materials such as silica, monocrystalline silicon, silicon oxynitride, silicate glasses such as tetraethylorthosilicate (TEOS), organic/polymeric materials, and the like. Other silicate glasses include phosphosilicate glass (PSG), fluorosilicate glass (FSG), borophosphosilicate glass (BPSG) and borophosphotetraethylorthosilicate

A019

(BPTEOS). The brittle nature makes the substrates and/or the OICs thereon readily susceptible to cracking and chipping, which often constitute fatal defects in the OICs (or substantially reduces the performance and/or reliability of the OICs).

5 The shape of the OICs on a given substrate is typically non-rectangular, but regular. Referring again to Fig. 1, a substrate with a plurality of OICs, in the case PLCs, is shown. When the shape of OICs is regular or consistent (substantially the same), they may be nested on the substrate to maximize the number of OICs fabricated on a given substrate. However, in order to maximize
10 yield, curvilinear cutting must be employed. The present invention permits curvilinear (a line that is curved, not straight) cutting of brittle materials.

 The stop crack is made in any suitable manner. For example, the crack may be formed using a saw, a milling machine, a laser, a water jet, or chemical etching. The stop cracks are made on the OICs at any time prior to dicing. In
15 this connection, the stop cracks may be formed before, during or after optical components are provided in the active regions of the substrate. The stop crack may remain empty after formation, or a material may be formed within the crack, such as providing silicon dioxide or other dielectric material in the crack. The stop crack may thus be a trench or a layer of a stop crack material.

20 The width of the stop crack is effective to deflect or prevent cracks and/or chips due to curvilinear cutting from propagating into the active region of the OIC. In one embodiment, the width of the stop crack is about 1 micron or more and about 1 mm or less. In another embodiment, the width of the stop crack is about 10 microns or more and about 0.5 mm or less. In yet another embodiment, the
25 width of the stop crack is about 25 microns or more and about 0.25 mm or less.

 The depth of the stop crack is effective to deflect or prevent cracks and/or chips due to curvilinear cutting from propagating into the active region of the OIC. In one embodiment, the depth of the stop crack is at least about 5% of the thickness of the OIC. In another embodiment, the depth of the stop crack is at

A019

least about 10% of the thickness of the OIC. In yet another embodiment, the depth of the stop crack is at least about 25% of the thickness of the OIC.

After the stop cracks are formed in the OICs, and after the optical components are formed in the active regions of the OICs, the substrate
5 containing a plurality of non-rectangular OICs is diced using curvilinear cutting to maximize the yield of non-rectangular OICs from the substrate. The substrate is cut by making the incision between stop cracks of adjacent OICs. Preferably, the stop cracks of adjacent OICs are substantially parallel and the cut edge or
10 incision is substantially parallel with the stop cracks. The substrate is diced in a curvilinear manner using any suitable cutting technique. For example, the substrate may be diced using a saw, a milling machine, a laser, or a water jet.

Although the invention has been shown and described with respect to certain illustrated implementations, it will be appreciated that equivalent alterations and modifications will occur to others skilled in the art upon the
15 reading and understanding of this specification and the annexed drawings. In particular regard to the various functions performed by the above described components (assemblies, devices, circuits, systems, etc.), the terms (including a reference to a "means") used to describe such components are intended to correspond, unless otherwise indicated, to any component which performs the
20 specified function of the described component (e.g., that is functionally equivalent), even though not structurally equivalent to the disclosed structure, which performs the function in the herein illustrated exemplary aspects of the invention. In this regard, it will also be recognized that the invention includes a system as well as a computer-readable medium having computer-executable
25 instructions for performing the acts and/or events of the various methods of the invention.

In addition, while a particular feature of the invention may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as

A019

may be desired and advantageous for any given or particular application. As used in this application, the term "component" is intended to refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and a computer. Furthermore, to the extent that the terms "includes", "including", "with", "has", "having", and variants thereof are used in either the detailed description or the claims, these terms are intended to be inclusive in a manner similar to the term "comprising."

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000